

PRO FORM

FILM FACED PLYWOOD

FOMEX[®]

Pro Form Film Faced Plywood can be used approximately 8-12 times which is best for the market that requires strict quality while having to maintain the most competitive pricing. With 100% grade core A and % WBP Melamine up to 18%. When using formwork, it helps save cost and time.

- Specialized for concrete formwork
- Good concrete surface
- 8-12 times uses



The mark of responsible forestry

FSC[®] A000504



Brand

FOMEX GREENWOOD

Standard sizes

1220x2440mm, 1250x2500mm, cut to size as buyer's request

Tolerant: +/- 0.5mm per meter

Standard thickness

12mm,15mm,17mm,18mm,

as buyer's request

Thickness tolerant: +/- 0.2mm - 0.5 mm

Surface

Phenolic Surface Film (PSF) on both side, back/brown color

Logo: Fomex GreenWood or as buyer's request

Core veneer

Hardwood: Acacia/Eucalyptus/Combine



Glue

Melamine/Phenol

Formaldehyde Emission Standard

E0/E1/E2

Moisture Content

<12% (less than twelve percent)

Wood material

Legally Source Plantation Wood

Origin

Vietnam

Pouring Number

Pro Form FFP is designed for use from 8-12 times

Edge color

Black, Red, Brown, as buyer's request

Density

610-625kg/m3

Packaging

Panels are packed in crates with metal straps then put into container by forklifts.

Thickness	Crate per container	Panel per Crate	Cubic meter per container
12mm	16	82	40-46
15mm	16	65	
17mm	16	58	
18mm	16	55	

***This is standard container packaging for international shipping for your reference.

FOMEX

GREEN WOOD | Produced by Fomex Group

MADE IN VIETNAM

FOMEX GROUP VIETNAM

Headquarter: Fomex Building, No.68/2, Luu Huu Phuoc Street, My Dinh I Ward, Nam Tu Liem District, Hanoi, Vietnam

Website: fomexgroup.vn

Email: Sales@fomexgroup.vn

Hotline: +84 877 034 666

