

# STANDARD

## FILM FACED PLYWOOD



Plywood can be used approximately 4-6 times which save cost for constructor. Standard Fomex Greenwood is a cost-effective film-faced plywood for concrete shuttering.

- Specialized for concrete formwork
- Cost-effective solution
- 4-6 times uses



The mark of responsible forestry  
FSC® A000504



### Brand

FOMEX GREENWOOD

### Standard sizes

1220x2440mm, 1250x2500mm, cut to size as buyer's request

Tolerant: +/- 0.5mm per meter

### Standard thickness

11.5mm, 12mm, 15mm, 17mm, 18mm,

as buyer's request

Thickness tolerant: +/- 0.2mm - 0.5 mm

### Surface

Phenolic Surface Film (PSF) on both side, back/brown color

Logo: Fomex GreenWood or as buyer's request

### Core veneer

Hardwood: Acacia/Eucalyptus/Combine



**Glue**

Melamine/Phenol

**Formaldehyde Emission Standard**

E0/E1/E2

**Moisture Content**

<12% (less than twelve percent)

**Wood material**

Legally Source Plantation Wood

**Origin**

Vietnam

**Pouring Number**

Standard FFP is designed for use from 4-6 times

**Edge color**

Black, Red, Brown, as buyer's request

**Density**

600-615kg/m3

**Packaging**

Panels are packed in crates with metal straps then put into container by forklifts.

Thickness	Crate per container	Panel per Crate	Cubic meter per container
12mm	16	82	40-46
15mm	16	65	
17mm	16	58	
18mm	16	55	

\*\*\*This is standard container packaging for international shipping for your reference.



MADE IN VIETNAM

**FOMEX GROUP VIETNAM**

**Headquarter:** Fomex Building, No.68/2,  
Luu Huu Phuoc Street, My Dinh I Ward, Nam  
Tu Liem District, Hanoi, Vietnam

Website: [fomexgroup.vn](http://fomexgroup.vn)

Email: [Sales@fomexgroup.vn](mailto:Sales@fomexgroup.vn)

Hotline: +84 877 034 666

