

SUPER FORM

FILM FACED PLYWOOD

FOMEX[®]

This is film-faced plywood with enhanced stability and service-ability, which promise consistency (alignment) of casting, and is suitable for exposed concrete area. Super Film Faced Plywood is made of high-quality tropical hardwood 100% veneer grade A, % WBP Melamine in glue up to 25%, customers can reuse 15-20 times.

- Specialized for concrete formwork
- Good concrete surface
- 15-20 times uses



The mark of
responsible forestry
FSC[®] A000504



Brand

FOMEX GREENWOOD

Standard sizes

1220x2440mm, 1250x2500mm, cut to size as buyer's request

Tolerant: +/- 0.5mm per meter

Standard thickness

12mm,15mm,17mm,18mm,

as buyer's request

Thickness tolerant: +/- 0.2mm - 0.5 mm

Surface

Phenolic Surface Film (PSF) on both side, back/brown color

Logo: Fomex GreenWood or as buyer's request

Core veneer

Hardwood: Acacia/Eucalyptus/Combine



Glue

Melamine/Phenol

Formaldehyde Emission Standard

E0/E1/E2

Moisture Content

<12% (less than twelve percent)

Wood material

Legally Source Plantation Wood

Origin

Vietnam

Pouring Number

Super Form FFP is designed for use from 15-20 times

Edge color

Black, Red, Brown, as buyer's request

Density

620 - 635 kg/m³

Packaging

Panels are packed in crates with metal straps then put into container by forklifts.

Thickness	Crate per container	Panel per Crate	Cubic meter per container
12mm	16	82	40-46
15mm	16	65	
17mm	16	58	
18mm	16	55	

***This is standard container packaging for international shipping for your reference.



MADE IN VIETNAM

FOMEX GROUP VIETNAM

Headquarter: Fomex Building, No.68/2,
Luu Huu Phuoc Street, My Dinh I Ward, Nam
Tu Liem District, Hanoi, Vietnam

Website: fomexgroup.vn

Email: Sales@fomexgroup.vn

Hotline: +84 877 034 666

