

WBP MELAMINE

COMMERCIAL PLYWOOD



WBP Commercial Plywood is a plywood with the same as ordinary commercial plywood, but the glue is used to bond Melamine WBP fillers, which makes the plywood resistant to boiling to until 8 hours but still not detached.



The mark of responsible forestry

FSC® A000504



Brand

FOMEX GREENWOOD

Standard sizes

1220mmx2440mm,

Standard thickness

11mm

Thickness tolerant: +/- 0.3mm

Surface

Bintangor

Core veneer

Hardwood: Acacia/Eucalyptus/Combine

Glue

WBP Melamine

MADE IN VIETNAM



Moisture Content

<12% (less than twelve percent)

Wood material

Legally Source Plantation Wood

Origin

Vietnam

Density

590 - 615 kg/m3

Packaging

Panels are packed in crates with metal straps then put into container by forklifts.

Thickness	Crate per container	Panel per Crate	Cubic meter per container
12mm	16	82	40-46
15mm	16	65	
17mm	16	58	
18mm	16	55	

***This is standard container packaging for international shipping for your reference.

**FOMEX GROUP VIETNAM**

Headquarter: Fomex Building, No.68/2,
Luu Huu Phuoc Street, My Dinh I Ward, Nam
Tu Liem District, Hanoi, Vietnam

Website: fomexgroup.vn

Email: sales@fomexgroup.vn

Hotline: +84 877 034 666

